



SIMATIC S7-1200 G2: SM 1232 analog output, 8 AO; outputs: 8x AQ 14 bit DAC (+/-10 V, 0-20 mA or 4-20 mA)

Figure similar

General information	
Product type designation	SM 1232, AQ 8x 14 bit
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption, typ.	45 mA
from backplane bus 5 V DC, typ.	90 mA
Power loss	
Power loss, typ.	5.6 W
Analog outputs	
Number of analog outputs	8; Current or voltage
Output ranges, voltage	
• -10 V to +10 V	Yes
Output ranges, current	
• 0 to 20 mA	Yes
• 4 mA to 20 mA	Yes
Load impedance (in rated range of output)	
• with voltage outputs, min.	1 000 Ω
• with current outputs, max.	600 Ω
Cable length	
• shielded, max.	100 m; shielded, twisted pair
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	14 bit; Voltage: 14 bit; Current : 13 bit
Errors/accuracies	
Temperature error (relative to output range), (+/-)	25 °C ±0.3 % / -20 °C to 60 °C ±0.6 % of the full-scale deflection
Basic error limit (operational limit at 25 °C)	
• Voltage, relative to output range, (+/-)	0.3 %
• Current, relative to output range, (+/-)	0.3 %
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
• Diagnostic alarm	Yes
Diagnoses	
• Monitoring the supply voltage	Yes
• Wire-break	Yes
• Short-circuit	Yes

Diagnostics indication LED		
• DIAG LED	Yes	
• for status of the outputs	Yes	
Degree and class of protection		
IP degree of protection	IP20	
Standards, approvals, certificates		
CE mark	Yes	
CSA approval	No	
UL approval	Yes	
cULus	Yes	
FM approval	No	
RCM (formerly C-TICK)	Yes	
KC approval	No	
Marine approval	No	
Ambient conditions		
Free fall		
• Fall height, max.	0.3 m; five times, in product package	
Ambient temperature during operation		
• min.	-20 °C	
• max.	40 °C; at max. voltages and max. specifications	
• horizontal installation, min.	-20 °C	
• horizontal installation, max.	60 °C; at rated voltages, 50 % of max. specification and alternate IO active	
• vertical installation, min.	-20 °C	
• vertical installation, max.	50 °C; at rated voltages, 50 % of max. specification and alternate IO active	
Ambient temperature during storage/transportation		
• min.	-40 °C	
• max.	70 °C	
Air pressure acc. to IEC 60068-2-13		
• Operation, min.	540 hPa	
• Operation, max.	1 140 hPa	
• Storage/transport, min.	540 hPa	
• Storage/transport, max.	1 140 hPa	
Altitude during operation relating to sea level		
• Installation altitude, min.	-1 000 m	
• Installation altitude, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual	
Relative humidity		
• Operation at 25 °C without condensation, max.	95 %	
Vibrations		
• Vibration resistance during operation acc. to IEC 60068-2-6	3.5 mm from 5 - 8.4 Hz, 1g from 8.4 - 150 Hz	
• Operation, tested according to IEC 60068-2-6	Yes	
Shock testing		
• tested according to IEC 60068-2-27	Yes; IEC 68, Part 2-27 half-sine: strength of the shock 15 g (peak value), duration 11 ms	
Pollutant concentrations		
• SO2 at RH < 60% without condensation	SO2: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60% condensation-free	
connection method		
required front connector	No	
Mechanics/material		
Enclosure material (front)		
• Plastic	Yes	
Dimensions		
Width	30 mm	
Height	125 mm	
Depth	100 mm	
Weights		
Weight, approx.	173 g	
Classifications		
	Version	Classification
eClass	14	27-24-22-01

eClass	12	27-24-22-01
eClass	9.1	27-24-22-01
eClass	9	27-24-22-01
eClass	8	27-24-22-01
eClass	7.1	27-24-22-01
eClass	6	27-24-22-01
ETIM	9	EC001420
ETIM	8	EC001420
ETIM	7	EC001420

Approvals / Certificates

General Product Approval	For use in hazardous locations
---------------------------------	---------------------------------------

[Manufacturer Declaration](#)



EG-Konf.



[KC](#)



RCM



UL

For use in hazardous locations	Environment
---------------------------------------	--------------------



IECEX



UL

[CCC-Ex](#)



EPD

last modified:

1/22/2025