

## Data sheet for SINAMICS V90

Article No. : 6SL3210-5FE11-0UF0



Figure similar

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Rated data

#### Input

Number of phases	3 AC
Line voltage	380 ... 480 V +10 % -15 %
Line frequency	45 ... 66 Hz

#### Output

Rated power	1.00 kW
Rated current (IN)	3.00 A
Max. output current	9.00 A

### Inputs / outputs

#### Standard digital inputs

Number	4
--------	---

#### Digital outputs

Number	2
--------	---

### Mechanical data

Degree of protection	IP20 / UL open type
Frame size	F5A
Net weight	1.85 kg
Width	80.0 mm
Height	180.0 mm
Depth	200.0 mm

### Ambient conditions

Cooling	natural convection
Installation altitude	1,000 m

#### Ambient temperature

Operation	0 ... 45 °C
Storage	-40 ... 70 °C

#### Relative humidity

Max. operation	90 %
----------------	------

### Standards

Compliance with standards	CE, KC, cULus, EAC, C-Tick (RCM)
---------------------------	----------------------------------

### Communication

Communication	PROFINET
---------------	----------



Figure similar

MLFB-Ordering data

6SL3210-5FE11-0UF0

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

Rated data		Ambient conditions	
<b>Input</b>		<b>Cooling</b>	natural convection
Number of phases	3 AC	<b>Installation altitude</b>	1000 m
Line voltage	380 ... 480 V +10 % -15 %	<b>Ambient temperature</b>	
Line frequency	45 ... 66 Hz	<b>Operation</b>	0 ... 45 °C
<b>Output</b>		<b>Storage</b>	-40 ... 70 °C
Rated power	1.00 kW	<b>Relative humidity</b>	
Rated current (IN)	3.00 A	<b>Max. operation</b>	90 %
Max. output current	9.00 A	<b>Standards</b>	
<b>Inputs / outputs</b>		<b>Compliance with standards</b>	CE, KC, cULus, EAC, C-Tick (RCM)
<b>Standard digital inputs</b>		<b>Communication</b>	
Number	4	<b>Communication</b>	PROFINET
<b>Digital outputs</b>			
Number	2		
<b>Mechanical data</b>			
<b>Degree of protection</b>	IP20 / UL open type		
<b>Frame size</b>	FSA		
<b>Net weight</b>	1.85 kg		
<b>Width</b>	80.0 mm		
<b>Height</b>	180.0 mm		
<b>Depth</b>	200.0 mm		